# MATERIAL SAFETY DATA SHEET

HEALTH - 2
FLAMMABILITY - 4
REACTIVITY - 0
PERSONAL PROTECTION -

ITY: 1738 LUB ALL



## SECTION I

MANUFACTURED FOR
PRO CHEM, INC
ADDRESS
1475 BLUEGRASS LAKES
PKWY
ALPHARETTA, GA
30201

EMERGENCY TELEPHONE NUMBER
404-740-2800
TELEPHONE NUMBER FOR INFORMATION
404-740-2800
DATE PREPARED
01/28/92

## SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL NAME: HEXANE
COMMON NAME:
OTHER LIMITS: N/A
CAS #: 110-54-3
OSHA PEL: 50
ACGIH THRESHOLD: 50
% OF RAW MATERIAL: 43

CHEMICAL NAME: PARAFFINIC PETROLEUM DISTILLATES
COMMON NAME:
OTHER LIMITS: STEL 10MG/M3
CAS #: 64742-65-0
OSHA PEL: 5MG/M3
ACGIH THRESHOLD: 5MG/M3
% OF RAW MATERIAL: 18

CHEMICAL NAME: ALIPHATIC HYDROCARBON MIXTURE
COMMON NAME:
OTHER LIMITS: N/A
CAS #: 64742-63-8
OSHA PEL: N/A
ACGIH THRESHOLD: 5MG/M3
% OF RAW MATERIAL: 2

CHEMICAL NAME: PROPANE/ISOBUTANE/N-BUTANE
COMMON NAME:
OTHER LIMITS: ASPHYXIANT
CAS #: 74-98-6
OSHA PEL: 1000
ACGIH THRESHOLD: 1000
% OF RAW MATERIAL: 25

CHEMICAL NAME: ZINC COMPOUND
COMMON NAME:
OTHER LIMITS: N/A
CAS #: UNKNOWN
OSHA PEL: N/A
ACGIH THRESHOLD: 5MG/M3
% OF RAW MATERIAL: 0.1-0.5

# MATERIAL SAFETY DATA SHEET

HEALTH - 2
FLAMMABILITY - 4
REACTIVITY - 0
PERSONAL PROTECTION -

IDENTITY: 1738 LUB ALL

CONTINUED PAGE 1 OF 3

## SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL NAME: 2-BUTOXYETHANOL

COMMON NAME:
OTHER LIMITS: N/A
CAS #: 111-76-2

OSHA PEL: 25(SKIN)
ACGIH THRESHOLD: 23(SKIN)
% OF RAW MATERIAL: 0.1-0.5

CHEMICAL NAME: PETROLATUM

COMMON NAME:
OTHER LIMITS: N/A
CAS #: 8009-03-8

OSHA PEL: NOT ESTABLISHED
ACGIH THRESHOLD: NOT ESTABLISHED
% OF RAW MATERIAL: 4

CHEMICAL NAME: NON-HAZARDOUS

COMMON NAME:
OTHER LIMITS: N/A
CAS #:

OSHA PEL: N/A
ACGIH THRESHOLD: N/A
% OF RAW MATERIAL: 7

## SECTION III - PHYSICAL DATA

BOILING POINT: -40 DEG F TO > 500 DEG F
APPEARANCE: CLEAR/SOLVENT
SOLUBILITY: NIL
SPECIFIC GRAVITY (H2O=1): 0.7
VAPOR PRESSURE (mm Hg.): ND
VAPOR DENSITY (AIR=1): HEAVIER THAN AIR 4.0

MELTING POINT: NA
EVAPORATION RATE(BUTYL ACETATE=1): 31

## SECTION IV - FIRE & EXPLOSION DATA

FLASH POINT: -40 DEG F TCC
FLAMMABILITY LIMIT: N/A
METHOD USED:

LEL: 1.8
UEL: 12.0

EXTINGUISHING MEDIA: USE WATER, FOG, DRY CHEMICAL OR CARBON DIOXIDE
SPECIAL FIREFIGHTING PROCEDURES:
AEROSOL CANS MAY RUPTURE WHEN HEATED

UNUSUAL FIRE AND EXPLOSION HAZARDS:
HEATED CANS MAY BURST