

1/3

MATERIAL SAFETY DATA SHEET

Best Ext. Oil Base Traffic Paint - White
MSDS #2444

SECTION I PRODUCT INFORMATION

PART NUMBERS: 13692, 27730
 MSDS DATE: 05/08/91
 MANUFACTURERS NAME: Kurfees Coatings
 ADDRESS: 201 East Market Street
 Louisville, KY 40202
 EMERGENCY PHONE NUMBER: (502) 584-0151
 DISTRIBUTOR:
 CHEMICAL NAME:
 FORMULA:
 CATEGORY:
 BRIEF DESCRIPTION:

SECTION II HAZARDOUS INGREDIENTS & EXPOSURE LIMITS

HAZARDOUS COMPONENT(S)	CAS #	%	LIMIT VALUES	
SILICUM CARBONATE	1317-65-3	50.00	PEL	15 mg/m3 total dust
			TWA	15 mg/m3 total dust
			PEL	5 mg/m3 respirable fraction
			TWA	5 mg/m3 respirable fraction
V N & P NAPHTHA	8032-32-4	30.00	TWA	300 ppm
			TWA	1,350 mg/m3
			STEL	400 ppm
			STEL	1,800 mg/m3
TITANIUM DIOXIDE	13463-67-7	12.00	PEL	15 mg/m3 total dust
			TWA	10 mg/m3 total dust
			PEL	5 mg/m3 respirable fraction
			TWA	5 mg/m3 respirable fraction

MINERAL SPIRITS 64475-85-0 2.00

SODIUM POTASSIUM ALUMINUM SILICATE 68476-25-5 8.00

2/3

Best Ext. Oil Base Traffic Paint - White
MSDS #2444

SECTION V HEALTH HAZARD DATA cont.

INGESTION:

No information given by manufacturer.

INHALATION:

Remove from exposure, treat symptomatically, and get medical attention.

SECTION VI REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID:

Not Applicable

INCOMPATIBILITY (materials to avoid):

Oxidizing materials can cause a vigorous reaction.

HAZARDOUS DECOMPOSITION PRODUCTS:

As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.

SECTION VII SPILL OR LEAK PROCEDURES / WASTE DISPOSAL

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Flush spill away with water spray. Small spills may be collected with absorbent material. Avoid breathing vapors and contact with liquid.

WASTE DISPOSAL:

Mix with a compatible chemical which is less combustible and incinerate. Observe all federal, state and local laws concerning health and pollution.

SECTION VIII SPECIAL PROTECTION

LOCAL EXHAUST: Recommended using spark-proof fans.

SPECIAL EXHAUST: None known.

OTHER EXHAUST: No information given by manufacturer.

MECHANICAL: Recommended.

PROTECTIVE GLOVES: Should be worn.

EYE PROTECTION: Safety glasses should be worn.

OTHER PROT. EQUIPMENT: Safety shower and eye bath in work area.

RESPIRATORY PROTECTION: A NIOSH-approved respirator for organic vapors should be worn if needed.

Best Ext. Oil Base Traffic Paint - White
MSDS #2444

SECTION VIII SPECIAL PROTECTION cont.

VENTILATION: Local: recommended using spark-proof fans.
Mechanical recommended.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS IN HANDLING AND STORAGE:

Material is classified as a flammable liquid. Keep away from heat, sparks, and open flame. Do not store above 120° F. Keep container closed and upright to prevent leakage. Containers should be grounded when pouring. Avoid free fall of liquid in excess of a few inches. Workmen should be required to use only non-ferrous tools and wear non-sparking shoes in areas where explosion hazards exist. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 ppm.

OTHER PRECAUTIONS:

Hazardous product residue may remain after the product has been removed from its container. Do not re-use empty container without commercial cleaning or reconditioning. See also 29 Code of Federal Regulation 1910.1000. Do not take internally. Keep out of the reach of children.

ADDITIONAL INFORMATION TO ADD ABOUT PRODUCT:

Reportable under SARA Title III, Section 313 Reporting.