



Gillette Medical Evaluation Laboratories

401 Professional Drive
Gaithersburg, Maryland 20879
301-590-9781

1/3

MATERIAL SAFETY DATA SHEET

NAME: LIQUID PAPER CORRECTION FLUID (WHITE AND COLORS, LPCF-4, LPCF-8, LPCF-9)

CAS NO: NA

Effective Date: 8/22/90 Rev: 1

A. IDENTIFICATION

Composition* 1,1,1-Trichloroethane (71-55-6) Titanium Dioxide (13463-67-7) Resin(s) Mineral Spirits (64741-65-7) Di(2-ethylhexyl)Phthalate (117-81-7) Mustard Oil (57-06-7) Colorant(s)	%	Formula: <u>Mixture</u>
		Molecular Weight: <u>NA</u>
		Synonyms <u>Liquid Paper</u>

B. PHYSICAL DATA

Boiling Point <u>165</u> °F <u>74</u> °C	Melting Point <u>NA</u> °F <u>NA</u> °C	Freezing Point <u>NA</u> °F <u>NA</u> °C
Specific Gravity (H ₂ O=1) <u>~1.7</u>	Vapor Density (air=1) <u>~4.5</u>	Vapor Pressure @ <u>68</u> °F <u>100</u> mmHg
Evaporation (<u>Ether</u> =1) <u>Slower</u>	Saturation in Air (by volume @ <u>NA</u> °F) <u>NA</u> %	Autoignition Temperature <u>NA</u> °F
% Volatiles (by volume) <u>~50</u>	Solubility in Water <u><1%</u>	pH <u>NA</u>

Appearance/Odor	<u>White or colored fluid with a pungent solvent odor</u>
Flash Point and Test Method(s)	<u>>200°F, >93°C (Closed Cup) Product is non-flammable.</u>
Flammable Limits in Air (% by volume)	(See Section H.) Lower <u>NA</u> % Upper <u>NA</u> %

C. REACTIVITY

Stability	Conditions to Avoid <u>Contact with open flame or other high temperature source.</u>	Polymerization	Conditions to Avoid <u>NA</u>
<u>stable</u> X		<u>may occur</u>	
<u>unstable</u>		<u>will not occur</u> X	
Incompatible Materials <u>For solvent: strong alkalis, oxidizers; aluminum, zinc and other reactive metals (e.g., potassium, sodium, magnesium).</u>		Hazardous Decomposition Products <u>Thermal degradation, e.g., open flame, can produce small amounts of phosgene, hydrogen chloride and chlorine.</u>	

*IF MULTIPLE INGREDIENTS, INCLUDE CAS NUMBERS FOR EACH. NA=NOT AVAILABLE

Footnotes:

Physical data, except % Volatiles and Specific Gravity, refers to 1,1,1-Trichloroethane.

D. — HEALTH HAZARD DATA

Occupational Exposure Limits (PEL'S, TLV'S, etc.)

8 Hour TWA's: 1,1,1-Trichloroethane - 350 ppm (OSHA/ACGIH)
Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)
Di(2-ethylhexyl)Phthalate - 5 mg/cu m (OSHA/ACGIH)
These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

Routes/Effects of Exposure

1. Inhalation No adverse effects anticipated from normal use. If vapors are deliberately concentrated and inhaled (abuse), following symptoms may occur: respiratory irritation, dizziness, drowsiness, headache, nausea, unconsciousness, cardiac sensitization (abnormal heartbeat), coma and death. (Mustard oil is added to the product as an abuse deterrent.)

2. Ingestion
No adverse effects anticipated from normal use. Depending on amount ingested, most of the symptoms described above may occur. Estimated LD₅₀ in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (Ref. Gosselin, Smith and Hodge, Clinical Toxicology of Commercial Products, 5th ed., 1984).

3. Skin
a. Contact
No adverse effects anticipated from normal use. Irritation may occur if contact is prolonged/repeated.

b. Absorption
No adverse effects anticipated from normal use. Solvent can be absorbed through skin (prolonged contact), but not likely in acutely toxic amounts. Estimated LD₅₀ in rabbits is greater than 5 ml/kg.

4. Eye Contact
Irritation

5. Other
See Statement Below

E — ENVIRONMENTAL IMPACT

- 1. Applicable Regulations
NA
- 2. DOT Hazard Class —
- 3. DOT Shipping Name —

Environmental Effects NA

Other: Based on animal feeding studies, Di(2-ethylhexyl)phthalate or DEHP is listed by IARC and NTP as a possible human carcinogen, if ingested. Normal use of this product would result in no ingestion of DEHP. There is no evidence of cancer due to isolated incidents of ingestion, such as accidental ingestion. A quantitative risk assessment demonstrates that DEHP in Liquid Paper is not a significant risk to humans because of its low concentration and low exposure potential.

F. — EXPOSURE CONTROL METHODS

Engineering Controls

None under normal use conditions.

Eye Protection

None under normal use conditions

Skin Protection

None under normal use conditions

Respiratory Protection

None under normal use conditions

Other

Product is non-hazardous when used as directed in an office/room with normal air circulation.

G. — WORK PRACTICES

Handling and Storage

No unusual handling or storage when used as directed; when stored in large quantities (as in warehouse), it should be in a well-ventilated, cool area..

Normal Clean Up

Pick up spills with towels, tissues, etc.

Waste Disposal Methods

Dispose in accordance with applicable federal, state and local laws.