



35-012  
35-032  
35-101  
35-105

35-155

**Dow U.S.A.**

The Dow Chemical Company  
Midland, Michigan 48667

# Material Safety Data Sheet

Packaged by: Quaker Supreme Chemical Corp.  
P.O. Drawer 77, Montgomery, AL 36101  
Telephone: 1-800-633-1916  
Product Code: 03386

Manufactured by: DOW Chemical U.  
Midland, MI 48  
Emergency Phone: 517-636-4400  
Page: 1

Product Name: ~~NAPA DOT 3 BRAKE FLUID~~

Effective Date: 04/07/92 Date Printed: 04/24/92

MSDS:002266


## 1. INGREDIENTS: (% w/w, unless otherwise noted)

Proprietary mixture of glycol ethers, polyglycols, glycols, oxidation inhibitors and corrosion inhibitors

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not 'Hazardous' per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

## 2. PHYSICAL DATA:

BOILING POINT: 430F, 221C minimum  
VAP PRESS: Low.  
VAP DENSITY: Not determined.  
SOL. IN WATER: Infinite.  
SP. GRAVITY: 1.03  
APPEARANCE: Light yellow liquid.  
ODOR: Mild odor.



## 3. FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT: 272F, 133C  
METHOD USED: PMCC

Flash point by COC is 280F, 138C.

### FLAMMABLE LIMITS

LFL: Not determined.  
UFL: Not determined.

EXTINGUISHING MEDIA: Water fog, carbon dioxide, dry chemical, foam. For large scale fires, alcohol resistant foams are preferred if available. General purpose synthetic foams or protein foams may function, but much less effectively. Water may be used to flush spills away from fire exposures and to dilute spills to non-flammable mixtures. If possible, contain fire run off water.

For large scale fires, direct water stream may cause violent frothing, but fine water spray may help control situation.

(Continued on page 2 , over)

(R) Indicates a Trademark of The Dow Chemical Company

\* An Operating Unit of The Dow Chemical Company

