MANUFACTURED BY: Master Products
Industrial Airpark
Orange City, Iowa 51041

REVISED: 17-OCT-91

1-2

EMERGENCY TELEPHONE # : 712-737-3435
712-737-4993

INFORMATION TELEPHONE # : 712-737-3435
712-737-4993

MFG. PRODUCT NUMBER: RX-0904
FORMERLY: LX-7327-C

PROPER SHIPPING NAME: PAINT

TRADE NAME: O.M. TM-4 PAINT REMOVER

O.M. TM-4 Paint Remover

II HAZARDOUS INGREDIENTS

MSG	INGREDIENT	CAS #	WT.%	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA CEILING	OSHA PEAK	LEL%	VAPOR PRESSURE
(1)	Mineral Spirits	64741-41-9	5	100 PPM		500 PPM			.7	2.0 mm
(1)	Toluene	108-88-3	10	100 PPM	150 PPM	200 PPM	300 PPM	500 PPM	1.3	23.0 mm
(1)	Synasol	64-17-5	5	1000 PPM					3.3	44 mm
(1)	Methanol	67-56-1	(5	200 PPM	250 PPM	200 PPM			6.0	96 mm
(1)	Methyl Ethyl Ketone	78-93-3	(5	200 PPM	300 PPM	200 PPM			1.8	70.6 mm
(2)	Methylene Chloride	75-09-2	70	100 PPM	500 PPM	500 PPM	1000 PPM	2000 PPM	NONE	340 mm

WARNING MESSAGES:

(1) Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys, and blood.

(2) Methylene chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. Methylene Chloride is listed in the National Toxicology Program (NTP) Annual Report of Carcinogens (latest edition) and has been found to be a possible human carcinogen in the International Agency for Research on Cancer (IARC) monographs.

III PHYSICAL DATA

BOILING RANGE: 102-380 degrees F. EVAPORATION RATE: *slower than ether*

PERCENT VOLATILE BY VOLUME: 96.29% WEIGHT PER GALLON: 9.43 LBS

VAPOR DENSITY: * heavier than air *

IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 19 degrees C. 66 degrees F. LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: CLASS 1B

DOT CLASSIFICATION (HAZARD CLASS): *flammable liquid*

EXTINGUISHING MEDIA: *carbon dioxide, dry chemical, or fire foam*

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from heat, sparks, and flame.

SPECIAL FIRE FIGHTING PROCEDURES: Water is unsuitable, but may be used to cool closed containers.

V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVEREXPOSURE:
ACUTE: Inhalation of vapors could cause respiratory irritation: Liquid could irritate or damage eyes.
CHRONIC: None recognized.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: consult physician

PRIMARY ROUTE(S) OF ENTRY: skin and inhalation

EMERGENCY AND FIRST AID PROCEDURES:
INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.
EYES: Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.
SKIN: Wipe off with towel. Remove remainder with mineral spirits, turpentine, or lacquer thinner. Wash with soap and water. Remove contaminated clothing.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire, burning and welding may generate carbon monoxide. Hydrogen Chloride and Phosgene gas may also be produced.

CONDITIONS TO AVOID: Fire, burning, and welding

----------***** VII SPILL OR LEAK PROCEDURES *****----------

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbant.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

----------***** VIII SPECIAL PROTECTION INFORMATION *****----------

RESPIRATORY PROTECTION: In confined areas of poor ventilation, use chemical cartridge respirator or self-contained breathing apparatus.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LFL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: None required except for prolonged contact.

EYE PROTECTION: Safety glasses or goggles if there is a danger of splashing or if product is applied by spraying.

OTHER PROTECTIVE EQUIPMENT: * none *

HYGIENIC PRACTICES: See section V.

----------***** IX SPECIAL PRECAUTIONS *****----------

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near heat, sparks, or flame.

OTHER PRECAUTIONS: * none *