CPF

MATERIAL NAME: Tire Mounting Lube

MSDS # 115

MATERIAL SAFETY DATA SHEET

40324

SECTION 1 – CHEMICAL PRODUCTS AND COMPANY IDENTIFICATION

CAMEL TIRE CARE PRODUCTS 500 South 48th Street E. Muskogee, Oklahoma 74403 (918) 687 - 5427	FOR EMERGENCY SOURCE INFORMATION CONTACT: • (918) 687 - 5427 • CHEMTREC: (800) 424-9300 • CANUTEC: (613) 996-6666 • SETIQ: 91-800-00-214

OTHER PRODUCT IDENTIFICATION: 12-097 Rub Lube 12-901 89-097 CQ40324

TRADE NAMES AND SYNONYMS: NOT APPLICABLE (N.A.) | **CHEMICAL FAMILY:** N.A.

SECTION 2 – COMPOSITION/INFORMATION OF INGREDIENTS

INGREDIENT	CAS NUMBER	PERCENTAGE (%)
Nonhazardous ingredients	N.A.	100

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

- Nonhazardous under normal processing conditions

ACUTE /CHRONIC: N.A.

SECTION 4 – FIRST AID MEASURES

This product should not require emergency procedures in those employees working with it. Should employees show signs of chemical exposure, move to fresh air. If not breathing, administer CPR.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: (Method Used) N.A.	**FLAMMABLE LIMITS:** N.A.
IGNITION SEVERITY: N.A.	**EXPLOSION SEVERITY:** N.A.
MINIMUM EXPLOSION CONCENTRATION: N.A.	**AUTOIGNITION TEMPERATURE:** Not Established

EXTINGUISHING MEDIA: Water sprinkler system, dry chemical, foam, or Carbon Dioxide (CO_2).

UNUSUAL FIRE AND EXPLOSION HAZARDS: None Known

HAZARDOUS DECOMPOSITION PRODUCTS: None Known

SPECIAL INSTRUCTIONS: As in any fire, wear self contained breathing apparatus pressure demand (NIOSH/MSHA approved) and full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

N.A.

SECTION 7 – HANDLING AND STORAGE

N.A.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: General ventilation should be sufficient

SKIN PROTECTION: If irritation exists, wear clothing and gloves to protect from skin contact

EYE PROTECTION: Safety Glasses

RESPIRATORY PROTECTION: None should be needed, but if signs of chemical exposure is observed, wear and NIOSH approved respirator

MATERIAL NAME: Tire Mounting Lube

MSDS # 115

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES	
BOILING POINT (760 MM HG): 260 °F (127 °C)	PERCENT VOLATILE BY VOLUME: 0
SPECIFIC GRAVITY (H_2O = 1): 1.03	MELTING POINT: N.A.
EVAPORATION RATE (BuAc = 1): N.A.	VAPOR DENSITY (AIR =1): N.A.
VAPOR PRESSURE : N.A.	SOLUBILITY IN WATER: Complete
APPEARANCE AND ODOR: Amber Paste with a soapy odor	
SECTION 10 - STABILITY AND REACTIVITY	
CHEMICAL STABILITY: Stable	CONDITIONS TO AVOID: None Known
MATERIAL TO AVOID: None	HAZARDOUS POLYMERIZATION: Will not occur
SECTION 11 - TOXICOLOGICAL INFORMATION	
N.A.	
SECTION 12 - ECOLOGICAL INFORMATION	
N.A.	
SECTION 13 - DISPOSAL CONSIDERATIONS	
Follow local, state and federal regulations	
SECTION 14 - TRANSPORTATION INFORMATION	
N.A.	
SECTION 15 - REGULATORY INFORMATION	
N.A.	
SECTION 16 - OTHER INFORMATION	
NFPA 704 LABEL: None Established	HMIS LABEL - None Established
MSDS REVISIONS: All Sections	
MSDS CREATION DATE: 11/1/94 REVISION: 02/10/97	

DISCLAIMER

The information above is believed to be accurate and represents the best information currently available to the Manufacturer and MSDS developer. However, we make no warranty of merchantability or any other warrant, express or implied, with respect to such information, and we assume no liability resulting from its use. User should make their own investigation to determine the suitability of the information for their particular purposes. In no way shall the Manufacturer or MSDS developer be liable for any claims, losses, or damage of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the Manufacturer or MSDS developer has been advised of the possibility of such damages.

MSDS DEVELOPER: Cass Willard, CIH

DATE: 2/10/97