MATERIAL SAFETY DATA SHEET
MAY BE USED TO COMPLY WITH
29 CFR 1910.1200

U.S. DEPARTMENT OF LABOR
OSHA
OMB NO. 1218-0072

08/09/90

ITEM:7150 DESCRIPTION: VANDEX B62

SECTION I - IDENTITY

Manufacturer Data:
ATCO MANUFACTURING CO.
1400 BARCLAY CIRCLE
MARIETTA GA 30060

Emergency Phone: 404-424-7550
Information Phone: 404-424-7550
Date Prepared: 7/24/90
Preparer: DEBI

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY

Hazardous Components:	OSHA PEL	ACGIH TLV	Other Limits	%
TOLUENE (CAS#108-88-3)		100 PPM		20-40
XYLENE (CAS#1330-20-7)		100 PPM		1-15
DIACETONE ALCOHOL (CAS#123-42-2)		50 PPM		1-15
ISOPROPHYL ALCOHOL (CAS#67-63-0)		400 PPM		1-15

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: ND
Vapor Pressure: 45 PSIG
Vapor Density: ND
Specific Gravity: 0.93
Melting Point:
Evaporation Rate: 1
Solubility in Water: COMPLETE
Appearance and Odor: CREAMY WHITE GEL-MILD ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: CONCENTRATE 64F TOC
Flammable Limits: Upper- Lower-
Extinguishing Media:
SPRAY EXTREMELY FLAMMABLE ;USE FOAM,DRY CHEMICAL,CO2
Special Fire Fighting Procedures:
NONE
Unusual Fire and Explosion Hazards:
NONE

SECTION V - REACTIVITY DATA

Stability: STABLE
Conditions to Avoid: DO NOT EXPOSE CAN TO HEAT OR TEMPERATURE ABOVE 120
Incompatibility:(Materials to Avoid):

ITEM:7150 DESCRIPTION: VANDEX B62

SECTION V - REACTIVITY DATA

Hazardous Decomposition or Byproducts:

Hazardous Polymerization:
Conditions to Avoid:

SECTION VI - HEALTH HAZARD DATA

Routes of Entry: Inhalation- Y Skin- Y Ingestion- Y
Health Hazards(Acute and Chronic):
SEE SECTION II FOR HAZARDOUS INGREDIENTS
Carcinogenicity: NTP? IARC MONOGRAPHS? OSHA Regulated?

Signs and Symptoms of Exposure:
EXCESSIVE PROLONGED INHALATION MAY RESULT IN DROWSINESS,HEADACHES,NAUSEA,,
PLUS EYE AND LUNG IRRITATION
Medical Conditions Generally Aggrivated By Exposure:

Emergency First Aid Procedures:
INHALATION:REMOVE TO FRESH AIR. INGESTION: SEE PHYSICIAN IMMEDIATLEY
SKIN/EYE: FLUSH WITH LOTS OF WATER

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Spilled Or Released:
SOAK UP APPROPRIATE ABSORBANT MATERIAL OR FLUSH WITH WATER
Waste Disposal Method:
IN ACCORDANCE WITH LOCAL,STATE,& FEDERAL REGULATIONS
Precautions To Be Taken In Handling and Storing:
DONT STORE WHERE TEMPERATURES EXCEED 120 F
Other Precautions:

SECTION VIII - CONTROL MEASURES

Type Of Respiratory Protection:
NONE REQUIRED AS LONG AS NOT USED IN SMALL CONFINED AREA
Ventilation: Local Exhaust- GENERAL VENTILATION ADEQUATE
Ventilation: Mechanical-
Ventilation: Special-
Ventilation: Other-
Protective Gloves: ONLY REQUIRED W/PROLONGED USE
Eye Protection: GOGGLES WHEN SPLASHING OCCURS

ITEM:7150 DESCRIPTION: VANDEX B62

SECTION VIII - CONTROL MEASURES

Other Protective Clothing Or Equipment:

Work/Hygienic Practices:
STANDARD INDUSTRIAL PRACTICES