

# MATERIAL SAFETY DATA SHEET



# S-550

## DEGREE OF HAZARD

4 = EXTREME  
3 = HIGH  
2 = MODERATE  
1 = SLIGHT  
0 = INSIGNIFICANT

## HMIS RATING

Health	2
Flammability	1
Reactivity	0
Personal Protection	G

Material Safety Data Sheet US Department of Labor  
Complies with USDL Safety and Health Regulations, (29 CFR 1910.1200)

### SECTION I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: S-550  
Chemical Family: Herbicide  
Revision Date: January 1, 2007  
Manufactured for: SKY Enterprises, Inc.  
PO Box 1764  
Kinston, NC 28503  
Emergencies: (800)-535-5053

### SECTION II. COMPOSITION/INFORMATION IN COMPONENTS

CAS NUMBER	CHEMICAL NAME	% BY WGHT.	OSHA PEL/ ACGIH TLV	SARA 302/304 (1)*	SARA 313 (2)*	STATE INFO (3)(4)	CERCLA RQ
68476-34-6	Fuel Oil	< 81.0	5 mg/m3 / 5 mg/m3	NO	NO	NO	
64742-94-5	Aromatic Hydrocarbon	< 13.0	100 ppm / 100 ppm	NO	NO	NO	
111-90-0	Diethylene Glycol Monoethyl Ether	< 5.0	n/e / n/e	NO	YES	NO	
314-40-9	Bromacil	0.98	n/e / n/e	NO	YES	NO	
1928-43-4	Isocetyl 2-ethylhexyl Ester of 2, 4-D	1.09	10 mg/kg / n/e	NO	YES	NO	
91-20-3	Naphthalene	< 2.0	n/e	NO	YES	(3)	100 lbs.

\*See Section 15 for more information

n/e=none established - n/a=not applicable

### SECTION III. HAZARDS IDENTIFICATION

**Emergency Overview:** WARNING: Combustible. Keep away from heat and flame. Harmful or fatal if swallowed. Vapor harmful. Harmful if absorbed through skin. Can cause nervous system depression. Amber-brown liquid with solvent odor.

**Primary Route of Entry:** Skin contact/absorption, inhalation, eye contact.

**Acute/Potential Health Effects:**

**EYES:** May cause mild eye irritation. Symptoms include stinging, tearing and redness.

**SKIN:** May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Absorption from prolonged or massive skin contact may cause poisoning.

**INHALATION:** Avoid breathing vapors or mists. May cause dizziness, nausea, headache or loss of consciousness.

**INGESTION:** Harmful or fatal if swallowed. Aspiration hazard-this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

**Chronic/Long Term Effects:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**Signs and Symptoms of Overexposure:** Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

**Target Organ Effects:** No data.

**Reproductive/Developmental Information:** WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Carcinogenic Information:** WARNING: This product contains a chemical known to the State of California to cause cancer.

### SECTION IV. FIRST AID MEASURES

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**Skin:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

# MATERIAL SAFETY DATA SHEET



## S-550

### DEGREE OF HAZARD

4 = EXTREME  
3 = HIGH  
2 = MODERATE  
1 = SLIGHT  
0 = INSIGNIFICANT

### HMIS RATING

Health	2
Flammability	1
Reactivity	0
Personal Protection	G

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.  
Ingestion: Seek medical attention immediately. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Do not leave individual unattended.

### SECTION V. FIRE FIGHTING MEASURES

Flash Point: > 130°F (CC Method)

Extinguishing Media: Dry chemical, CO<sub>2</sub> or foam is recommended.

Special Fire Fighting Instructions: Wear a self contained breathing apparatus with a full face-piece operated in the positive pressure demand mode with chemical resistant personal protective equipment.

### SECTION VI. ACCIDENTAL RELEASE MEASURES

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Absorb spill with inert material (e.g. dry sand, earth). Eliminate all ignition sources. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

### SECTION VII. HANDLING AND STORAGE

Follow all MSDS/label precautions even after container is emptied because they may contain product residues. Use with adequate ventilation. Do not get in eyes, on skin or on clothing. Store in a cool, dry place. Keep container closed when not in use. Keep out of reach of children.

### SECTION VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene), clothing and boots.

Respiratory Protection: When respiratory protection is required, use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 and ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

### SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Amber-brown liquid with solvent odor.

Solubility in Water: Insoluble

pH Concentrate: N/A

Evaporation Rate (Butyl Acetate=1): N/E

Vapor Pressure (mmHg): N/E

Specific Gravity (H<sub>2</sub>O=1): 0.88

Vapor Density (Air=1): N/E

Boiling Point: 430°F

### SECTION X. REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid: High Temperature

Hazardous Decomposition Products: CO, CO<sub>2</sub>

Incompatibility: Acids and strong oxidizers

### SECTION XI. TOXICOLOGICAL INFORMATION

Acute Oral: >5g/kg (rat), Acute Inhalation: LC<sub>50</sub> >2.03 mg/L (4hr-rat), Acute Dermal: LD<sub>50</sub> >2g/kg (rabbit),

Primary Dermal: Toxicity Category IV

### SECTION XII. ECOLOGICAL INFORMATION

Bromacil: 96 hr LC<sub>50</sub>, fathead minnow: 182 mg/L

Toxic to aquatic invertebrates.

### SECTION XIII. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

# MATERIAL SAFETY DATA SHEET



## S-550

### DEGREE OF HAZARD

4 = EXTREME  
3 = HIGH  
2 = MODERATE  
1 = SLIGHT  
0 = INSIGNIFICANT

### HMIS RATING

Health	2
Flammability	1
Reactivity	0
Personal Protection	G

## SECTION XIV. TRANSPORTATION INFORMATION

D.O.T. Shipping Name/Class: Not regulated for ground domestic shipments.

## SECTION XV. REGULATORY INFORMATION

US Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Title III Section 311/312 Hazardous Categories – 40 CFR 370.2:

Acute (X) Chronic (X) Fire (X) Pressure ( ) Reactive ( ) Not Applicable ( )

(1) Title III Section 302/304 Extremely Hazardous Substances -40 CFR 355 Appendix A

(2) Title III Section 313 Toxic Chemicals – 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Codes(s) D001, D016.

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations.

(3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986)

(4) Massachusetts (Hazardous Substance Disclosure by Employers)

## SECTION XVI. OTHER INFORMATION

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.